

Model	<span style="color: green;">■</span> =Electric	<span style="color: orange;">■</span> =Engine	JCPT2223DC	JCPT2223RTB
<b>Size</b>				
Max. Working Height			22.00m	22.00m
Max. Platform Height			20.00m	20.00m
Overall Length			4.95m	4.95m
Overall Width			2.46m	2.46m
Overall Height(Rails Up)			3.86m	3.86m
Overall Height(Rails Down)			3.00m	3.00m
Platform Size(Length×Width)			4.59×2.25m	4.59×2.25m
Platform Extension Size			2.70m	2.70m
Ground Clearance(Stowed/Raised)			0.40m	0.40m
Wheelbase			3.30m	3.30m
Turning Radius(Inside/Outside)			1.25m/3.40m	1.25m/3.40m
Tyres			36×14-20	36×14-20
<b>Performance</b>				
S.W.L			750kg	750kg
S.W.L On Extension			750kg	750kg
Max. Occupants			4	4
Gradeability			30%	40%
Travel Speed(Stowed)			5.0km/h	5.0km/h
Travel Speed(Raised)			0.4km/h	0.4km/h
Max. Working Slope			2°/3°	2°/3°
Up/Down Speed			90/75sec	90/75sec
<b>Weight</b>				
Overall Weight			13400kg	13000kg
<b>Power</b>				
Diesel Engine			/	DEUTZ D2.9 L4 36.4kW/2600rpm
Diesel Tank			/	100L
Hydraulic Tank			150L	150L
Battery			48V/630Ah	/
Charger			48V/60A	/
Driving Motor			4×AC 32V/3.3kW	/
Lifting Motor			2×DC 48V/10.0kW	/
<b>Other Configurations</b>				
4×4 Driving 4×4 Steering Self-leveling Hydraulic Outriggers Automatic Unidirectional Extended Platform Drivable At Full Height				

Model	<span style="color: green;">■</span> =Electric	<span style="color: orange;">■</span> =Engine	JCPT2212DC	JCPT1912DC
<b>Size</b>				
Max. Working Height			22.00m	19.00m
Max. Platform Height			20.00m	17.00m
Overall Length			4.72m	4.72m
Overall Width			1.25m	1.25m
Overall Height(Rails Up)			3.82m	3.57m
Overall Height(Rails Down)			2.99m	2.74m
Platform Size(Length×Width)			4.30×1.19m	4.3m×1.19m
Platform Extension Size			1.80m	1.80m
Ground Clearance(Stowed/Raised)			0.20m/0.02m	0.20m/0.02m
Wheelbase			3.18m	3.18m
Turning Radius(Inside/Outside)			1.6m/2.3m	1.6m/2.3m
Tyres			28×10-22	28×10-22
<b>Performance</b>				
S.W.L			600kg	750kg
S.W.L On Extension			600kg	750kg
Max. Occupants			2	2
Gradeability			25%	25%
Travel Speed(Stowed)			3.0km/h	3.0km/h
Travel Speed(Raised)			0.5km/h	0.5km/h
Max. Working Slope			1°(0°)	1°(0°)
Up/Down Speed			80/75sec	80/75sec
<b>Weight</b>				
Overall Weight			12350kg	11750kg
<b>Power</b>				
Hydraulic Tank			130L	130L
Battery			48V/630Ah	48V/630Ah
Charger			48V/60A	48V/60A
Driving Motor			4×AC 32V/3.3kW	4×AC 32V/3.3kW
Lifting Motor			2×DC 48V/8.0kW	2×DC 48V/8.0kW
<b>Other Configurations</b>				
4×4 Driving 4×4 Steering Self-leveling Hydraulic Outriggers Automatic Pothole Protection Device Drivable At Full Height				